

Mission Specialist Pro 5

The **Mission Specialist Series Pro 5** utilizes a system of interchangeable, modular components residing on a single, intelligent network. This topology provides an extremely flexible and customizable platform which can be easily adapted to target specific missions. It is this flexibility which sets apart the Mission Specialist ROV Series from current technology in the Remotely Operated Vehicle Industry.



Specifications

| | |
|---------------------------------------------|----------------------------------|
| Power Requirements: | 110/220 VAC (1 to 2.4 kW) |
| Total System Weight (Sub & OCC): | 25.2 kg (55.5 lb) |
| Cases: | 2-3 Watertight Rugged Hard Cases |
| Owner's Manual: | Online Digital |
| System Tool Kit: | Included |
| Communications Protocol: | RS-485 and Ethernet |
| Warranty: | 2 Year Comprehensive |



Camera

| | |
|-------------------------|--------------------------------------------------------------------------------------------------------------|
| High Definition: | With Ethernet interface (IP) |
| Video: | up to 1920 x 1080, 25 fps |
| Mechanical: | Standard VideoRay 9 pin connection Ethernet, 12 VDC, RS-485 Auto or Manual Focus Optical Glass Dome |
| Features: | White Balance Control up to 16x Digital Zoom (64 steps) 13 Megapixel Still Image Capture |
| Sensitivity: | Less than 1 lux (standard) |
| View Angle: | 160° Tilt (180° FoV) Horizontal: 136° Vertical: 92° |
| Compression: | MJPEG |



Power

400 VDC power module
1500 W @ 48 VDC
Full monitoring of input voltage, output current, temperature



Submersible

Depth Rating:

- Up to 305 m (1,000 ft)

Size (l x w x h):

- 51.49 x 33.02 x 25.73 cm
(20.31 x 13.00 x 10.13 in)

Weight:

- 11.8 kg (26 lb) without ballast

Ballast:

- Modular

Case:

- 24.6 x 19.4 x 13.8 in
(62.5 x 49.3 x 35.1 cm)
less than 22.7 kg (50 lb) with
submersible and payload



Buoyancy

Float: 305 m rated



Operator Control Console (OCC)

Power Input: 90-260 VAC (47-440 Hz)
Power Output: 400 VDC, 2400 W
Display: HD Daylight Viewable Monitor
Weight: 15.2 kg (33.6 lb)
Case: Water tight
0.62 x 16.87 x 8.12 in
(52.37 x 42.85 x 20.62 cm)
Processing: Integrated i7 system processor
Controller: Industrial Programmable Hand Controller
Safety: Integral Line Isolation
Monitor Emergency
Kill Switch
Ports: 7 external USB ports
1 external Ethernet port



Communications

3 x 100 Mbps Ethernet ports
3 x RS-485 ports
Power control and monitoring



Propulsion

Brushless thruster with integrated controller

2 Vectored Horizontal Thrusters
Forward: 20.3 kg (44.7 lb)
1 Vertical Thruster
Max speed: > 4.4 knots



Lighting

LED

2 independent light arrays (38 Watts max ea.)
60° spot beam
110° flood beam
Each array can be individually controlled
3,000 K CCT, 80 CRI White
7,600 total lumens per LED light module
15,200 lumens total light



IMU

9 DOF IMU and magnetic compass

Pressure based depth sensor:
100 Bar, with 400 Bar optional
0.2° Static Roll/Pitch
0.5° Dynamic Roll/Pitch
1.0° Yaw
18°/h Gyro Bias Stability



For more details about our accessories,
visit [VideoRay.com](https://www.VideoRay.com).